

# EUROTUBI

Eurotubi Pressfitting System è un sistema di tubi e raccordi per la realizzazione di impianti idrotermosanitari destinati alla conduzione di acqua, gas, aria compressa.

I raccordi presentano all'estremità una camera toroidale, all'interno della quale è alloggiato un anello di gomma EPDM in grado di sopportare alte pressioni e temperature superiori a 80 gradi.

Tubi e raccordi vengono assemblati per mezzo di pinze elettromeccaniche che imprime una deformazione permanente.

La guarnizione, una volta compressa, garantisce una giunzione perfettamente ermetica e non divisibile.

La tecnologia pressfitting abbina l'assoluta efficacia delle giunzioni all'estrema semplicità e rapidità di posa in opera, non essendo richieste saldature, incollaggi o filettature.

I maggiori costi del materiale sono pertanto largamente bilanciati dai contenuti costi di manodopera.

Eurotubi Pressfitting System è disponibile in acciaio Inox AISI 316L e Acciaio al Carbonio, con una gamma di raccordi compresa tra 15 e 108 mm di diametro.

La qualità dei materiali impiegati, costanti test di tenuta e di durata e l'adozione di un rigoroso sistema di controllo qualità, hanno permesso all'Eurotubi Pressfitting System di ottenere la conformità alle più severe certificazioni europee.

*Eurotubi Pressfitting is a system of tubes and fittings used for hydrothermosanitary installations recommended for the conveyance of water, gas, compressed air.*

*The fittings present at the extremities the o-ring seating, where the rubber seal of high use resistance is allocated, able to support high pressures and temperatures over 80° C.*

*Tubes and fittings are assembled through the permanent deformation of the fitting by the special pressing jaws mounted on the small electromechanical tools. Once pressed, the o-ring guarantees the perfectly hermetical and not divisible connection.*

*The pressfitting system combines the extreme reliability of the joints with the easy and quick way of laying as it does not need any gluing, threading or welding. As a consequence, the major costs of material are fully balanced by the extremely low cost of labour. Eurotubi Pressfitting System is available in Stainless Steel 316L and in Carbon Steel, in the range of fitting diameters from 15 mm to 108 mm.*

*The quality of used materials, constant sealing and duration tests and the adoption of a rigorous quality control allowed Eurotubi Pressfitting system to obtain the conformity with the strictest European certifications.*



**EUROTUBI**  
**PRESSFITTING**<sup>®</sup>  
SYSTEM

**EUROTUBI EUROPA S.r.l.**

Via Croce Rossa Italiana, 12  
20054 Nova Milanese (MI)

Tel. +39 0362 365068

Fax +39 0362 41099

[info@eurotubieuropa.it](mailto:info@eurotubieuropa.it)

[www.eurotubieuropa.it](http://www.eurotubieuropa.it)

